



Technical Data Sheet

Cutable Heat Transfer Vinyl - EASY EP

EASY EP is designed for cad-cutting application.

AVAILABLE TYPES

- EASY EP(VT-01~33): Normal & Basic colors
- EASY EP NEON (FL-01~05) : Neon colors
- EASY EP PASTEL (PVT-01~10) : Pastel colors

SPECIFICATION

- Thickness (excluding 100mic. PET liner) : 170-180mic.
- Size : 510mm*25m per roll, 510mm*50m per roll



PACKING

Individual paper box per roll plus pallet packing

- Volume :
 - 0.5m * 50m : 180*180*525mm, 11kg
 - 0.5m * 25m : 155*155*525mm, 5.5kg

TRANSFER CONDITION

- Temperature: 140°C(284°F) ~ 150°C(302°F)
- Pressing time: 8~10 seconds
- Pressure: about 30kg
- Peeling condition: Cool peel

HOW TO USE

1. Cut the image in mirror on hotmelt side
2. Weed the useless parts
3. Heat & pressure applied
4. Remove PET carrier backing film when it is cool

RECOMMENDED FABRICS

100% cotton, 100% polyester
Poly/cotton blends, Acrylics

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr