

Technical Data Sheet

Elastic Foil

- With more patterns

Elastic Foil is hot stamping foil's color layer on which polyester hotmelt is applied. Because it has only color layer and hotmelt, Elastic Foil is very elastic and soft.

SPECIFICATION

- Thickness(excluding 100micron PET liner): 85mic.

- Size: 0.5m(20") * 50m(54.68yd) per roll

- Packing detail: 155*155*525mm, 7kg/carton (1 roll=1 carton)

TRANSFER CONDITION

Temperature: 150°C(302°F)
Pressing time: 10 seconds
Remove PET Carrier Film
Pressure: about 30kg
Peeling condition: Cool peel

RECOMMENDED FABRICS

100% cotton, 100% polyester Poly/cotton blends, Acrylics



All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

ADDRESS: 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947 TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr