



## Technical Data Sheet

## Foam PU (Cutttable)

This HTV is polyurethane based funky puffy vinyl which rises after heat pressing and maintains awesome foaming effect. Foam PU is highly suitable for letter as below pictures.



### SPECIFICATION

- Thickness(excluding 100micron PET liner): 150-155 micron
- Size: **510mm\*25m per roll**

### TRANSFER CONDITION

- Temperature: 140°C
- Pressing time: 6 seconds
- Pressure: low
- Peeling condition: remove transfer tape immediately

### HOW TO USE

1. Cut the film in mirror image
2. Weed the useless parts
3. Place the film on the garment
4. Heat apply
5. Remove application tape when it is hot

### AVAILABLE COLORS

19 colors

### RECOMMENDED FABRICS

100% cotton, 100% polyester Poly/cotton blends, Acrylics

*All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.*

LAST UPDATED 01/2022

### **MINSEO COATING FELX CO., LTD.**

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947  
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr