



Technical Data Sheet

Cuttable Heat Transfer Vinyl - Glow In Dark

PU based thermal transfer film designed for cad-cutting application

AVAILABLE COLORS

Glow in Dark(GD-01~06)

SPECIFICATION

- Thickness(excluding 100micron PET liner): 140micron
- Size: 0.51m(20.15") * 25m(27.34yd) or 50m(54.68yd) per roll

PACKING

Individual paper box per roll plus pallet packing

- Volume :
 - 0.5m * 50m : 180*180*525mm, 11.5kg
 - 0.5m * 25m : 155*155*525mm, 6kg

TRANSFER CONDITION

- Temperature: 140°C(284°F) ~ 150°C(302°F)
- Pressing time: 8 seconds
- Pressure: about 30kg
- Peeling condition: Cool peel

HOW TO USE

1. Cut the film in mirror image
2. Weed the useless parts
3. Place the film on the garment
4. Heat apply
5. Remove application tape when it is warm

RECOMMENDED FABRICS

100% cotton, 100% polyester
Poly/cotton blends, Acrylics



All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr