



Technical Data Sheet

OPAL (Cutttable)

OPAL heat transfer vinyl is PET film based high gloss with opalescent sheen.



SPECIFICATION

- Thickness(excluding 120micron PET liner)
: about 110 micron
- Size: 0.49m(19.29") * 50m(54.68yd) per roll

TRANSFER CONDITION

- Temperature: 150°C
- Pressing time: 10 seconds
- Pressure: about 30kg
- Peeling condition: Cool peel

**** This opalescent effect can be shown better on bright fabric rather than dark fabric.**

HOW TO USE

1. Cut the film in mirror image
2. Weed the useless parts
3. Place the film on the garment & Heat press
4. Remove application tape when it is cool

AVAILABLE COLORS

4 colors



Red(OP-01) Orange(OP-02) Green(OP-03) Purple(OP-04)

RECOMMENDED FABRICS

100% cotton, 100% polyester Poly/cotton blends, Acrylics

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr