



Technical Data Sheet

SUB BLOCK PU Cutttable Heat Transfer Vinyl

Sub Block PU(Poly-urethane) thermal transfer films designed for cad-cutting application which specifically designed for complete blocking dye migration.

AVAILABLE COLORS

6 colors (white, neon yellow, neon orange, neon pink, neon green, neon blue)

SPECIFICATION

- Thickness(excluding 100micron PET liner): 90mic. (30mic. PU, 60mic. Hotmelt)
- 100micron PET liner
- Size: 510mm*25m per roll or 510mm*50m per roll

PACKING

Individual paper box per roll plus pallet packing

- Volume :
 - 0.5m * 50m : 155*155*525mm, 9kg
 - 0.5m * 25m : 135*135*525mm, 4.5kg

TRANSFER CONDITION

- Temperature: 140°C(284°F) ~ 150°C(302°F)
- Pressing time: 8 seconds
- Pressure: about 30kg
- Peeling condition: Hot peel



HOW TO USE

1. Cut the image in mirror on hotmelt side
2. Weed the useless parts
3. Heat & pressure applied
4. Remove PET carrier backing film when it is hot

RECOMMENDED FABRICS

100% cotton, 100% polyester
Poly/cotton blends, Acrylics

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr