



PRODUCT INFORMATION

Printable Heat Transfer Vinyl - Printable Sub Block

Printable Sub Block is specifically designed for complete blocking dye migration.
Sub Block can be used for vivid color effect on garments with no color migration.

SPECIFICATION

-Thickness (excluding 100mic. PET liner) : 90mic. (30mic. PU, 50-60mic. Hotmelt)
-3" inner paper core

PACKING

Individual paper box per roll plus pallet packing

- Volume :

510mm * 50m : 155*155*525mm, 9kg

510mm * 25m : 135*135*525mm, 4.5kg

TRANSFER CONDITION

- Temperature: 140°C(284°F) ~ 150°C(302°F)

- Pressing time: 8~10 seconds

- Pressure: about 35 PSI

- Peeling condition: Hot peel

HOW TO USE

1. Print and cut the image in positive on surface.
2. Weed the useless parts
3. Remove the image from the PET liner using an application tape.
4. Positioned on garment
5. Heat & pressure applied
6. Remove application tape when it is hot

RECOMMENDED FABRICS

100% cotton, 100% polyester

Poly/cotton blends, Acrylics

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

LAST UPDATED 01/2022

MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947

TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr